

## I. General Purpose Rectifier

### 6.0A Silicon Rectifier

#### 6A05~6A10

(Package: R-6)

<p><b><u>FEATURES</u></b></p> <ul style="list-style-type: none"> <li>• The plastic package carries Underwriters Laboratory Flammability Classification 94V-0</li> <li>• Construction utilizes void-free molded plastic technique</li> <li>• Low reverse leakage</li> <li>• High forward surge current capability</li> <li>• High temperature soldering guaranteed : 250 /10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3 kg) tension</li> </ul> <p><b><u>MECHANICAL DATA</u></b></p> <ul style="list-style-type: none"> <li>• Case : R-6 molded plastic body</li> <li>• Terminals : Plated axial leads, solderable per MIL-STD-750, Method 2026</li> <li>• Polarity : Color band denotes cathode end</li> <li>• Mounting Position : Any</li> <li>• Weight : 0.072 ounce, 2.05 grams</li> </ul>	<p>Case: R-6 Dimensions in inches and (millimeters)</p>
--	---

## Ratings & Electrical Characteristics

Characteristic	Symbol	6A05	6A1	6A2	6A4	6A6	6A8	6A10	Units
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length at $T_a = 60$	$I_o$	6.0							Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	400.0							Amps
Maximum instantaneous forward voltage at 6.0A	$V_F$	0.95							Volts
Maximum DC reverse current $T_a = 25$ at rated DC blocking voltage $T_a = 100$	$I_R$	10.0 400							$\mu A$
Typical junction capacitance (Note 1)	$C_j$	150							pF
Typical thermal resistance (Note 2)	Rth-JA	10.0							/ W
Operating junction and storage temperature range	$T_j, T_{stg}$	-65 to +175							

Note :

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. Thermal resistance from junction to ambient at 0.375"(9.5mm) lead length, P.C.B mounted

# Ratings and Characteristic Curves of 6A05~6A10

