

VII. Switching Diode

SMD Type (SOD-123) BAV19W~BAV21W

(Package: SOD-123)

<p>FEATURES</p> <ul style="list-style-type: none"> • Fast switching speed. • Ideally suited for automated assembly processes. • For general purpose switching applications. • High conductance. <p>MECHANICAL DATA</p> <ul style="list-style-type: none"> • Case : Molded plastic, SOD-123 • Mounting position : Any • Polarity : Color band denotes cathode <p>DEVICE MARKING CODE</p> <ul style="list-style-type: none"> • BAV19W : A8 • BAV20W : T2 • BAV21W : T3 	<p>Case: SOD-123 Dimensions in millimeters</p>
---	--

Ratings & Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20%.

Characteristic	Symbol	BAV19W	BAV20W	BAV21W	Unit
Non-Repetitive peak reverse voltage	V_{RM}	120	200	250	Volts
Peak repetitive reverse voltage	V_{RRM}	100	150	200	Volts
Working peak reverse voltage	V_{RWM}				
DC reverse voltage	V_R				
RMS reverse voltage	$V_{R(RMS)}$	71	106	141	Volts
Forward voltage (Max)	V_F		1.00 1.25		Volts
		$I_F=100mA$	$I_F=200mA$		
Reverse breakdown voltage (Min) (@ $I_R=100\mu A$)	$V_{(BR)R}$	120	200	250	Volts
Average rectified output current	I_o	200			mA
Non-repetitive peak forward surge current	I_{FSM}	4.0			Amps
		@ $t=1.0\mu s$			
Maximum reverse leakage current	I_R	$V_R=100V$	0.1	-	-
		$V_R=150V$	-	0.1	-
		$V_R=200V$	-	-	0.1
Power dissipation	P_D	250			mW
Junction capacitance (Max) $V_R=0V, f=1.0MHz$	C_j	5			PF
Reverse recovery time (Max) $I_F=I_R=30mA, I_{RR}=0.1 * I_R, R_L=100$	T_{rr}	50			ns
Typical thermal resistance, junction to ambient air	R_{th-JA}	500			/W
Operating and storage temperature range	T_j, T_{stg}	-65 to +150			

Ratings and Characteristic Curves of BAV19W/ BAV20W/ BAV21W

