

I. General Purpose Rectifier

1.0A Surface Mount Silicon Rectifier S1A ~ S1M

(Package: SMA (DO-214AC))

<p><u>FEATURES</u></p> <ul style="list-style-type: none"> • The plastic package carries Underwriters Laboratory Flammability Classification 94V-0 • For surface mounted applications • Low reverse leakage • Built-in strain relief, ideal for automated placement • High forward surge current capability • High temperature soldering guaranteed : 250 /10 seconds at terminals <p><u>MECHANICAL DATA</u></p> <ul style="list-style-type: none"> • Case : JEDEC DO-214AC molded plastic body • Terminals : Solder plated, solderable per MIL-STD-750, Method 2026 • Polarity : Color band denotes cathode end • Mounting Position : Any • Weight : 0.081 grams 	<p>Case: SMA Dimensions in inches and (millimeters)</p>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------

Ratings & Electrical Characteristics

Characteristics	Symbol	S1A	S1B	S1D	S1G	S1J	S1K	S1M	Units
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum average forward rectified current at $T_L = 110$	I_O	1.0							Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	30.0							Amps
Maximum instantaneous forward voltage at 1.0 A	V_F	1.1							Volts
Maximum DC reverse current $T_a = 25$ at rated DC blocking voltage $T_a = 100$	I_R	5.0 50.0							μA
Typical junction capacitance (Note 1)	C_j	15.0							PF
Typical thermal resistance (Note 2)	R_{th-JA}	75.0							/ W
Operating junction and storage temperature range	T_j, T_{stg}	-65 to + 175							

Notes:

1. Measured at 1MHz and applied reverse voltage of 4.0 V D.C.
2. P.C.B. mounted with 0.2 x 0.2" (5.0 x 5.0mm) copper pad areas

Ratings and Characteristic Curves of S1A~S1M

