


# I. General Purpose Rectifier

## 2.0A Surface Mount Silicon Rectifier S2A~S2M

(Package: SMB (DO-214AA))

<p><b><u>FEATURES</u></b></p> <ul style="list-style-type: none"> <li>The plastic package carries Underwriters Laboratory Flammability Classification 94V-0</li> <li>For surface mounted applications</li> <li>Low reverse leakage</li> <li>Built-in strain relief, ideal for automated placement</li> <li>High forward surge current capability</li> <li>High temperature soldering guaranteed : 250 /10 seconds at terminals</li> </ul> <p><b><u>MECHANICAL DATA</u></b></p> <ul style="list-style-type: none"> <li>Case : JEDEC DO-214AA molded plastic body</li> <li>Terminals : Solder plated, solderable per MIL-STD-750, Method 2026</li> <li>Polarity : Color band denotes cathode end</li> <li>Mounting Position : Any</li> <li>Weight : 0.138 grams</li> </ul>	 <p style="text-align: center;">Case: SMB Dimensions in inches and (millimeters)</p>
---	--

## Ratings & Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20%.

Characteristic	Symbol	S2A	S2B	S2D	S2G	S2J	S2K	S2M	Units
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	Volts
Maximum average forward rectified current at $T_L = 90$	$I_O$	2.0							Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	50.0							Amps
Maximum instantaneous forward voltage at 2.0 A	$V_F$	1.1							Volts
Maximum DC reverse current at rated DC blocking voltage $T_a = 25$ $T_a = 100$	$I_R$	5.0 200.0							$\mu A$
Typical junction capacitance (Note 1)	$C_j$	30.0							pF
Typical thermal resistance (Note 2)	Rth-JA	50.0							/ W
Operating junction and storage temperature range	$T_j, T_{stg}$	-65 to +175							

Notes:

1. Measured at 1MHz and applied reverse voltage of 4.0 V D.C.
2. P.C.B. mounted with 0.2 x 0.2" (5.0 x 5.0mm) copper pad areas

# Ratings and Characteristic Curves of S2A~S2M

