

II. Schottky Rectifier

3.0A Surface Mount Schottky Rectifier S32~S320


(Package: SMA (DO-214AC))

FEATURES

- The plastic package carries Underwriters Laboratory flammability classification 94V-0
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency
- High forward surge current capability
- High temperature soldering guaranteed : 250 /10 seconds at terminals

MECHANICAL DATA

- Case : JEDEC DO-214AC molded plastic body
- Terminals : Solder plated, solderable per MIL-STD-750, method 2026
- Polarity : Color band denotes cathode end
- Mounting Position : Any
- Weight : 0.058 grams



Case: SMA
Dimensions in inches and (millimetres)

Ratings & Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20%.

Characteristic	Symbol	S32	S33	S34	S35	S36	S38	S310	S315	S320	Units
Maximum repetitive peak reverse voltage	V_{RRM}	20	30	40	50	60	80	100	150	200	Volts
Maximum RMS voltage	V_{RMS}	14	21	28	35	42	56	70	105	140	Volts
Maximum DC blocking voltage	V_{DC}	20	30	40	50	60	80	100	150	200	Volts
Maximum average forward rectified current at TL (see Fig. 1)	I_O	3.0									Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	70									Amps
Maximum instantaneous forward voltage at 3.0A DC	V_F	0.55		0.70		0.85		0.95		Volts	
Maximum DC reverse current at rated DC blocking voltage $T_a = 25^\circ\text{C}$ $T_a = 100^\circ\text{C}$	I_R	0.5						1.0		mA	
		20		10							
Typical junction capacitance (Note 1)	C_j	500			300			PF			
Typical thermal resistance (Note 2)	R_{th-JA}	55						62		$^\circ\text{C/W}$	
Operating junction temperature range	T_j	-65 to +125			-65 to +150			$^\circ\text{C}$			
Storage temperature range	T_{stg}	-65 to +150									$^\circ\text{C}$

Notes:

1. Measured at 1 MHz and applied reverse voltage of 4.0 volts D.C.
2. P.C.B. mounted with 0.2 x 0.2" (5.0 x 5.0mm) copper pad areas.

Ratings and Characteristic Curves of S32~S320

