

## II. Schottky Rectifier


### 5.0A Surface Mount Schottky Rectifier S55L~S56L

#### FEATURES

- Metal-Semiconductor junction with gard ring
- Epitaxial construction
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0
- For use in low vlotage, high frequency inverters, free wheeling, and polarity protection applications

#### MECHANICAL DATA

- Case: Molded Plastic
- Polarity:Color band denotes cathode



Dimensions in inches and (millimeters)

#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

CHARACTERISTICS	SYMBOL	S55L	S56L	UNIT
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	50	60	V
Maximum RMS Voltage	V <sub>RMS</sub>	35	42	V
Maximum DC Blocking Voltage	V <sub>DC</sub>	50	60	V
Maximum Average Forward Rectified Current 0.375" (9.5mm) Lead Lengths	I <sub>(AV)</sub>	5.0		A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load(JEDEC Method)	I <sub>FSM</sub>	150		A
Maximum Forward Voltage at 5.0A DC	V <sub>F</sub>	0.55		V
Maximum DC Reverse Current @T <sub>J</sub> =25°C at Rated DC Bolcking Voltage @T <sub>J</sub> =100°C	I <sub>R</sub>	1.0 50		mA
Typical Junction Capacitance (Note1)	C <sub>J</sub>	350		pF
Typical Thermal Resistance (Note2)	R <sub>θJA</sub>	10		°C/W
Operating Temperature Range	T <sub>J</sub>	-55 to +150		°C
Storage Temperature Range	T <sub>STG</sub>	-55 to +150		°C

NOTES: 1.Measured at 1.0 MHz and applied reverse voltage of 4.0V DC

2.Thermal resistance junction to ambient,

# RATING AND CHARACTERISTIC CURVES S55L THRU S56L

FIG. 1 – FORWARD CURRENT DERATING CURVE




FIG. 2 – MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 – TYPICAL JUNCTION CAPACITANCE




FIG.4-TYPICAL FORWARD CHARACTERISTICS




FIG.2-TYPICAL REVER CHARACTERISTICS

